

Horizontal

Type	BD/BC-108	BD/BC-138
Gross capacity	108 liters	138 liters
Dimension (height×length×width) mm	910X625X490 (Packaging size: 955X680X560)	910X815X490 (Packaging size: 955X870X560)
Voltage	12/24V DC current: ≤5.0A + 10%	12/24V DC current: ≤5.5A + 10%
Average power consumption	≤60W + 15%	≤68W + 15%
Temperature range	8°C to ≥-18°C (Variable via electronic thermostat)	
Weight	Net: 27.5 kg	Net: 31 kg
Refrigerating Fluid	R134a	
Refrigeration capacity	Arrived -18°C In 2hours. (Under the standard running condition and rated load)	
Other features	Digital temperatuer-control panel. The compressor could adjust the torque and rotate speed automatically.	



BD/BC-158



BCD-178

Horizontal

Type	BD/BC-158	BD/BC-178
Gross capacity	158 liters	178 liters
Dimension (height×length×width) mm	910X875X520 (Packaging size: 955X935X575)	910X955X520 (Packaging size: 955X1015X575)
Voltage	12/24V DC current: ≤6.0A + 10%	12/24V DC current: ≤6.3A + 10%
Average power consumption	≤70W + 15%	≤75W + 15%
Temperature range	8°C to ≥-18°C (Variable via electronic thermostat)	
Weight	Net: 37kg	Net: 39 kg
Refrigerating Fluid	R134a	
Refrigeration capacity	Arrived -18°C in 2hours. (Under the standard running condition and rated load)	
Other features	Digital temperatuer-control panel. The compressor could adjust the torque and rotate speed automatically.	



BD/BC-258



Horizontal

Type	BD/BC-258
Gross capacity	258 liters
Dimension (height×length×width) mm	905X1245X665 (Packaging size: 950X1300X685)
Voltage	12/24V DC current: ≤7.5A + 10%
Average power consumption	≤85W + 15%
Temperature range	8°C to ≥-15°C (Variable via electronic thermostat)
Weight	Net: 54 kg
Refrigerating Fluid	R134a
Refrigeration capacity	Arrived -12°C in 3hours. (Under the standard running condition and rated load)
Other features	Digital temperatuer-control panel. The compressor could adjust the torque and rotate speed automatically.

12/24V=DC DISPLAY CUPBOARD
Vertical SC-258



BCD-210



Vertical

Type	BCD-210
Gross capacity	210 liters
Dimension (height×length×width) mm	1601X589X526 (Packaging size: 1670X635X585)
Voltage	12/24V DC current: ≤6.5A + 10%
Average power consumption	≤75W + 15%
Temperature range	8°C to ≤-18°C (Variable via electronic thermostat)
Weight	Net: 48 kg
Refrigerating Fluid	R134a
Refrigeration capacity	Arrived -16°C in 2hours. (Under the standard running condition and rated load)
Other features	Digital temperatuer-control panel. The compressor could adjust the torque and rotate speed automatically.



SC-258

Vertical

Type	SC-258
Gross capacity	258 liters
Dimension (height×length×width) mm	1665X570X560 (Packaging size: 1730X655X640)
Voltage	12/24V DC current: ≤6.0A + 10%
Average power consumption	≤65W + 15%
Temperature range	8°C to ≥-4°C (Variable via electronic thermostat)
Weight	Net: 52 kg
Refrigerating Fluid	R134a
Refrigeration capacity	Arrived 4°C in 4hours. (Under the standard running condition and rated load)
Other features	Digital temperatuer-control panel. The compressor could adjust the torque and rotate speed automatically.